



bollard 1

ADVANTAGES

- Architectural stylish appearance
- Choice of colour

APPLICATION



- Walkways, pedestrian path
- Square, architectural & landscape

FEATURES


- Corrosion resistant die-cast aluminium body component.
- Corrosion resistant extruded aluminium profile.
- Prismatic polycarbonate diffuser with UV stabilized additive.
- Anodized sand blasted aluminium reflector. Stainless steel screws.
- Integral control gear. Chromatized surface pre-treatment.
- Polyester powder coat with UV stabilized component.
- Standar colour: Black.
- Option Colour: Silver, White.

CHARACTERISTICS


- Optical assembly : IP 54
- Ballast Compartment : IP 54
- Electrical Insulation : Class 1
- Voltage : 220V~240V
- Wattage : 18W~23W
- Lamp Type : PLC and TC-TSE
- Dimensions (mm) : $\phi 175(L) \times 985(H)$
*height: approx 600mm on request
- Approx. Net weight : 6~8kg



dimension (mm)



PLC 1x26W



Model No.	Description	Voltage	Frequency	Lamp
GPCP0568	BOLLARD 1 23W TC-TSE C/W Lamp	220-240V	50-60Hz	E27
GPCP0569	BOLLARD 1 1x26W PLC C/W Gear & Lamp	220-240V	50-60Hz	G24d3
GPCP0570	BOLLARD 1 1x18W PLC C/W Gear & Lamp	220-240V	50-60Hz	G24d2

ordering information