

Other models available upon request. Specifications are subject to change without prior notice.




**NYLON INSULATED CRIMPING TERMINALS
COPPER TINNED - 105°C**



Ring

Type	Section mm ² (AWG)	Ø mm screw	F	B	A	E	L	d	D	s	Tool	Packing pcs
BM 80107	0,25 ÷ 1,5 (22-16)	3	3,20	8	10,4	8,6	22,2	1,95	4,20	0,8		1000
BM 80113		3,5	3,60	8	10,4	7,80	22,2	1,95	4,20	0,8		1000
BM 80119		4	4,20	8	10,4	7,50	22	1,95	4,20	0,8		1000
BM 80125		5	5,20	8	10,4	8	22,4	1,95	4,20	0,8		1000
BM 80131		6	6,20	10	10,4	8,6	23,70	1,95	4,20	0,8		1000
BM 80137		8	8,30	14	10,4	12,60	30	1,95	4,20	0,8		1000
BM 80143		10	10,40	14	10,4	12,80	30	1,95	4,20	0,8		1000
BM 80207	1,5 ÷ 2,5 (16-14)	3	3,20	8	11	8	23	2,45	4,80	0,8		1000
BM 80213		3,5	3,70	8	11	8	23	2,45	4,80	0,8		1000
BM 80219		4	4,20	8	11	8	23	2,45	4,80	0,8		1000
BM 80225		5	5,20	9	11	7,50	23,60	2,45	4,80	0,8	536	1000
BM 80231		6	6,20	10,50	11	9,80	26	2,45	4,80	0,8	166	1000
BM 80237		8	8,20	15	11	14,50	33	2,45	4,80	0,8	534	1000
BM 80243		10	10,50	15	11	14,50	33	2,45	4,80	0,8		1000
BM 80319	2,5 ÷ 6 (12-10)	4	4,20	8	14	8,4	26,5	3,50	6,60	1		500
BM 80325		5	5,20	10	14	8,5	27,5	3,50	6,60	1		500
BM 80331		6	6,20	11	14	11	30,6	3,50	6,60	1		500
BM 80337		8	8,20	15	14	15,3	37	3,50	6,60	1		500
BM 80343		10	10,5	19	14	16,5	40	3,50	6,60	1		500

Round Pin




Type	Section mm ² (AWG)	B	E	A	L	d	D	Tool	Packing pcs
BM 80150	0,25 ÷ 1,5 (22-16)	1,8	12	10,4	22	1,95	4,20	536	1000
BM 80250	1,5 ÷ 2,5 (16-14)	1,8	12	11	23	2,45	4,80	166	1000
BM 80350	2,5 ÷ 6 (12-10)	2,6	14	14	28	3,6	6,60	534	500

Other models available upon request. Specifications are subject to change without prior notice.



**NYLON INSULATED CRIMPING TERMINALS
COPPER TINNED - 105°C**



Fork

Type	Section mm ² (AWG)	Ø mm screw	F	B	A	E	L	d	D	s	Tool	Packing pcs	
BM 80108	0,25 ÷ 1,5 (22-16)	3	3,20	5,6	10,4	6,7	20	1,95	4,20	0,8		1000	
BM 80114		3,5	3,70	6,5	10,4	6,5	19,4	1,95	4,20	0,8		1000	
BM 80120		4	4,20	6,4	10,4	6,3	20,9	1,95	4,20	0,8		1000	
BM 80126		5	5,20	8	10,4	8	21,2	1,95	4,20	0,8		1000	
BM 80132		6	6,20	9,20	10,4	8,3	22,4	1,95	4,20	0,8		1000	
BM 80208		1,5 ÷ 2,5 (16-14)	3	3,20	5,6	11	8,4	23	2,45	4,80	0,8		1000
BM 80214			3,5	3,70	6,60	11	5,3	20,3	2,45	4,80	0,8	536	1000
BM 80220	4		4,20	6,60	11	5,3	20,3	2,45	4,80	0,8	166	1000	
BM 80226	5		5,20	9,10	11	9,5	25	2,45	4,80	0,8	534	1000	
BM 80232	6		6,30	10	11	11,2	27	2,45	4,80	0,8		1000	
BM 80314	2,5 ÷ 6 (12-10)	3,5	3,70	8,10	14	7,2	26	3,50	6,60	1		500	
BM 80320		4	4,20	8,10	14	7,2	26	3,50	6,60	1		500	
BM 80326		5	5,20	9	14	10,5	28,5	3,50	6,60	1		500	
BM 80332		6	6,30	11	14	11	29,5	3,50	6,60	1		500	
BM 80338		8	8,20	15,20	14	15	35,2	3,50	6,60	1		500	
BM 80344		10	10,50	19	14	16,6	38	3,50	6,60	1		500	

Butt Connector Nylon Insulated



Type	Section mm ² (AWG)	B	L	d	D	Tool	Packing pcs
BM 80160*	0,25 ÷ 1,5 (22-16)	15	26	1,8	4,2		1000
BM 80260*	1,5 ÷ 2,5 (16-14)	15	26	2,5	4,8	536	1000
BM 80360*	2,5 ÷ 6 (12-10)	15	27	3,7	6,5	166	500
BM 80460	10	26	43	4,8	8,2	534	100
BM 80560	16	29	46	6	9	521	100
BM 80660	25	29	46	7	11,50		100